



Technical data sheet (TDS)

Company identity: STAR PLY Gabon

Bp: 1024 GSEZ / Nkok Libreville B2 /B1

Customer service: starplygabon@gmail.com

N°02-STP-MG-25-01-23

Trade name	OKOUGREEN	
Intended	Marine craft, vehicle bodies, building works in structural and non-structural exterior applications with regular and prolonged weather and water exposure	
System of AVCP	System 2+	
Harmonized standard	EN 13986:2004+A1:2015	
Notified body	BBA UK 0836	
Plywood specification	BS 1088 : 2018	
Bonding quality	EN 314-2 CLASS 3	
Release of formaldehyde	Conforms to regulation of TSCA Title VI emission <0.001 ppm	
Reaction to fire thickness 10-40mm	D-s2,d0 (500kg/m3)	
Water vapour permeability μ	Wet cup μ	Dry cup μ
	70	200
Airborne sound insulation	NPD	
Mechanical Durability	NPD	
Thermal conductivity	0.13	
Specie	100% OKOUME (Aucoumea klaineana)	



Essential characteristics	Strength and stiffness for structural use (bending)	Harmonised technical specifications
	Performances	
Strength and stiffness for structural use (bending) Thickness 8 mm 10mm 15mm 18mm 25mm 40mm	F 40/25 E 50/30 F 25/30 E 40/50 F 30/30 E 40/50 F 25/30 E 40/50 F 25/25 E 40/40 F 25/20 E 50/40	BS EN 13986:2004+A1:2015

The performance of the product identified above is in conformity with the set declared performance.
 This declaration of performance is issued, in accordance with regulation (EU) 305/2011.under the sole responsibility of the manufacturer by

Manager quality and certifications

Libreville on 09-05-2023

Carl ANGONE

(Place and date of issue)



Carl